

VERTICAL TRAILER-MOUNT MIXER

with 2 Speed Gearboxes **VR-2-Speed Series**
Narrow Body

[SPECIFICATION SHEET]

Customer Name: _____ **Company Name:** _____

Date: _____ **Model:** _____

Options for all Two-Speed Trailers		Yes	Price
BASE PRICE			
1	Upgrade Floor Thickness: Twin Auger: _____ 3/4" - 1"		
2	Stainless Steel Floor Upgrade from 3mm to 5mm		
3	8" Belting Extension _____ Single Screw _____ Twin Screw		
4	8" Cut-out Option (per side) _____ LHS _____ RHS _____ Both Sides		
5	Steel Extension (1/4" material) _____ 12" _____ 20" _____ Other		
6	Rear Door for Premix _____ Standard (50" W x 32.5" H) _____ Ex Large (60"W x 32.5"H)		
7	Side-Door and Slide-Chute (Per Door) Front: _____ LHS _____ RHS Rear: _____ LHS _____ RHS		
8	Extra Kicker (Per Auger) _____ Front _____ Rear		
9	Scale Installation		
10	Power Cord		
11	Two-speed Shifting Cable		
12	Electric Shifting Option on two-speed Gear Box		
13	Stainless Steel Sides _____ 2mm _____ 2.5mm _____ 3.0 mm		
14	Rear Light and Feeding Light		
15	Light package built-into rear bumper (LED)		
16	Non-Standard Paint Color _____ Custom Decal _____		
17	Door Indicator Gauge: _____ One Door _____ Additional Doors		
18	Telescopic Discharge (Hydraulic)		
19	Tilting Discharge _____ Hydraulic 36" _____ Hydraulic 42"		
20	Magnets on Slide Chute		
21	Battery with Enclosure		
22	Viewing Platform		
23	Discharge Incline Option		
24	Discharge Extension Option: _____ 6" _____ 12" _____ 18"		
25	Extra Discharge Motor for Right-hand side		
26	Tandem Axles and Spring Suspension		
27	Heavy-duty Single-Point Suspension (Up-Grade)		
28	Upgrade from Standard Tandem Axles to Single-Point Suspension		
29	Tri-Dem Axles (3) Axles Two Steering – One fixed with brakes		
30	6" of Stainless Steel Lining on each Auger _____ 3mm _____ 5mm		
31	Complete Stainless Steel Lining on each Auger _____ 3mm _____ 5mm		
32	Feedlot-Style Folding Spout		
33	Dogleg Discharge Conveyor _____ (79" + 30") _____ (90" + 30")		
34	Constant Velocity (CV) PTO		
35	UHMW Plastic Rails on Discharge w/overhead support brackets-Requires Option 18		
36	C2082H Roller Chain (Up-Charge)		
37	Up-Grade from 17.5" tires to 22.5" Tires (Per Axle)		
38	Swing Gate for dual-sided discharge conveyor		
39	3-position drop chute (Steel + rubber)		
40	Stationary drop chute (No magnets)		
41	Discharge overhead support brackets		
Scale System: Indicator _____ Remote _____ 2nd Remote _____ Other _____			
Hitch Pin: Single Lip _____ Double Lip _____ Pin Size _____			
PTO Specs – 1 3/8" _____ 1 3/4" _____ 540 _____ 1000 _____			
Blade Option: 2-piece _____ Busatis _____ Feedlot Backing Plate _____			
Credit For: _____ No Discharge Conveyor _____ No Front Door _____ No St Steel Liner on Floor			()