

# VERTICAL TRAILER-MOUNT Direct Drive Series

## [ SPECIFICATION SHEET - WIDE BODY ]

Customer Name: \_\_\_\_\_ Company Name: \_\_\_\_\_

Date: \_\_\_\_\_ Model: \_\_\_\_\_

Options for all Direct Drive Trailers		Yes	Price
<b>BASE PRICE</b>			
1	Upgrade Floor Thickness: Single Auger: ___ 3/4"- 1" Twin: ___ 5/8"- 3/4" ___ 3/4"- 1"		
2	Stainless Steel Floor Upgrade from 3mm to 5mm		
3	8" Belting Extension _____ Single Screw _____ Twin Screw		
4	8" Cut-out Option (per side) _____ LHS _____ RHS _____ Both Sides		
5	Steel Extension (1/4" material) _____ 12" _____ 20" _____ Other		
6	Rear Door for Premix _____ Standard (50" W x 32.5" H) _____ Ex Large (60"W x 32.5"H)		
7	Side-Door and Slide-Chute (Per Door) Front: ___ LHS ___ RHS Rear: ___ LHS ___ RHS		
8	Extra Kicker (Per Auger) _____ Front _____ Rear		
9	Scale Installation		
10	Power Cord		
11	Stainless Steel Sides _____ 2mm _____ 2.5mm _____ 3.0 mm		
12	Rear Light and Feeding Light		
13	Light package built-into rear bumper (LED)		
14	Non-Standard Paint Color _____ Custom Decals _____		
15	Door Indicator Gauge: _____ One Door _____ Additional Doors		
16	Telescopic Discharge (Hydraulic)		
17	Tilting Discharge _____ Hydraulic 36" _____ Hydraulic 42"		
18	Magnets on Slide Chute		
19	Battery with Enclosure		
20	Viewing Platform		
21	Discharge Incline Option		
22	Discharge Extension Option: _____ 6" _____ 12" _____ 18"		
23	Extra Discharge Motor for Right-hand side		
24	Tandem Axles and Spring Suspension		
25	Heavy-duty Single-Point Suspension (Up-Grade)		
26	Upgrade from Standard Tandem Axles to Single-Point Suspension		
27	Tri-Dem Axles (3) Axles Two Steering – One fixed with brakes		
28	6" of Stainless Steel Lining on each Auger _____ 3mm _____ 5mm		
29	Complete Stainless Steel Lining on each Auger _____ 3mm _____ 5mm		
30	Feedlot-Style Folding Spout		
31	3-position drop chute (Steel + rubber)		
32	Stationary drop chute (No magnets)		
33	Dogleg Discharge Conveyor _____ (79" + 30") _____ (90" + 30")		
34	UHMW Plastic Rails on Discharge w/overhead support brackets-Requires Option 16		
35	C2082H Roller Chain (Up-Charge)		
36	Up-Grade from 17.5" tires to 22.5" Tires (Per Axle)		
37	Swing Gate for dual-sided discharge conveyor		
38	Constant Velocity (CV) PTO		
39	ZDB Auto-shift transmission Part #60019960		
40	Discharge Overhead Support Brackets		
Scale System: Indicator _____ Remote _____ 2nd Remote _____ Other _____			
Hitch Pin: Single Lip _____ Double Lip _____ Pin Size _____			
PTO Specs – 1 3/8" _____ 1 3/4" _____ 540 _____ 1000 _____			
Blade Option: 2-piece _____ Busatis _____ Feedlot Backing Plate _____			
<b>Credit For:</b> _____ No Discharge Conveyor _____ No Front Door _____ No St Steel Liner on Floor		(	)